

NozzTeq Inc.



(800) 705-8845

SALES@UTILITYINSIGHT.NET

NozzTeq root cutters and impact cutters have raised drain and sewer cleaning to new levels.

NozzTeq™ is first and foremost a problem solver and systems supplier.

Come to us with your problem in the field of Pipe cleaning and we will develop a tailor-made solution. We are not satisfied with something which merely meets the technical specifications – products must do their job in practice. To achieve that goal, everything we manufacture undergoes extensive tests. That is how NozzTeq™ creates new possibilities for you as our customer.

Throughout the years in cooperation NozzTeq™ has created a number of new sewer and drain cleaning products, some so unique that they have been patented. Over time, those same products have become an obvious choice for everyone who works with water jetting and pipe cleaning.

Yesterday's innovations from NozzTeq™ are taken for granted today. We are continually creating new sewer cleaning products which in the same self-evident way to make life easier for our customers.

Paikert™ / Intruder™ Cutter

The Paikert™/Intruder™ is a low speed, high torque impact cutter designed for more severe blockages. When conventional cutters simply can't cut it, consider the Paikert™/Intruder. Paikert™/Intruders have successfully been in use worldwide for over 25 years.



The machine is the most capable on the market due to its patented "Hydro-Torque" impact drill motor. It's designed to work with today's sewer jetting machines and does not require lubrication after use. So, whether you've got a pipe full of hardened concrete, stubborn chemical or mineral deposits, protruding taps or thick heavy root growth in large pipes, the Paikert™/Intruder is your best alternative.

Lumberjack™ Cutters

The Lumberjack™ is a high speed (up to 50,000 rpm), low torque multi purpose cutter. The rotation of the Lumberjack™ is powered by the water pressure supplied by a common sewer jetting or combination truck. Although it is designed to cut roots, many of our customers use it for cutting concrete, grease, mineral and chemical deposits, tuberculation and protruding laterals. We know of no other cutter that is as versatile, reliable and user friendly for common, everyday cutting jobs. The Lumberjack™ series operates in pipe sizes from 3" (75 mm) up to 48" (1200 mm).



The bearings are sealed, grease lubricated and water cooled. No lubrication is required after use. It works and works with very little maintenance or care required. The standard and optional cutting accessories are designed to eliminate potential pipe damage. The low torque high-speed feature prevents the cutter from getting stuck, spinning off the hose or cutting through the host pipe.

The Lumberjack™ cutters are available in different models for optimal cleaning effect. The cutters remove roots and other common obstructions in sanitary and storm sewer pipe in accordance with the following model number.

LJ050

Weight: 2 lbs

Length: 4,8"

Sled sizes: 3",4" (optional 5" and 6")

Connecting thread: ½" BSP or ½" NPT

Minimum flowrate: 10 GPM

Bursting pressure: 10 000 PSI





LJ075

Weight: 9 lbs
 Length: 9,5"
 Sled sizes:
 4",6" (optional 8" and 9")
 Connecting thread: 1/2" female BSP or 1/2" female NPT
 Minimum flowrate: 15 GPM
 Bursting pressure: 10 000 PSI



LJ175

Weight: 10 lbs
 Length: 9"
 Sled sizes: 6" (optional 8" and 9")
 Connecting thread: 1/2" female BSP or 1/2" female NPT
 Minimum flowrate: 15 GPM
 Bursting pressure: 6 000 PSI



LJ100

Weight: 13 lbs
 Length: 12"
 Sled sizes: 4", 6" (optional 8" and 9")
 Connecting thread: 1" or 1 1/4" female BSP or 1" or 1 1/4" female NPT
 Minimum flowrate: 35 GPM
 Bursting pressure: 10 000 PSI



LJ200

Weight: 25 lbs
 Length: 15"
 Sled sizes: 6", 8" & 10" (optional 12")
 Connecting thread: 1 1/4" female BSP or 1 1/4" female NPT
 Minimum flowrate: 45 GPM
 Bursting pressure: 10 000 PSI



LJ300

Weight: 47 lbs
 Length: 24"
 Sled sizes: 8", 10", 12" (optional to 21")
 Connecting thread: 1" or 1 1/4" female BSP or 1" or 1 1/4" female NPT
 Minimum flowrate: 45 GPM
 Bursting pressure: 10 000 PSI



LJ700

Weight: 98 lbs+
 Length: 43"
 Sled sizes: 16" up to 36" (optional to 48")
 Connecting thread: 1" or 1 1/4" female BSP or 1" or 1 1/4" female NPT
 Minimum flowrate: 100 GPM
 Bursting pressure: 6 000 PSI



NozzTeq offers a 10 Year Limited Warranty with the JAWS® Sewer nozzle, and 5 Year Limited warranty with the Hammerhead™ sewer nozzle!