



Rausch Options & Accessories

• Point Repair

Quick-Lock Point Repair System

Quick-Lock is a strictly mechanical spot repair system for the partial repair on the inner pipe. It is applicable in common sewage, well and potable water lines. Key to this system is its patented locking mechanism, which once is locked gives the sleeve its structural strength and presses the rubber gasket against the inner pipe wall.



• Lateral Jetting

TSS200 Lateral Flushing Attachment for Lateral Launch System

The Portable flushing attachment for the cleaning of laterals from the main line. Uses the same principles as lateral inspection. Application range for mainlines of 8 to 48 inches and lateral lines of 4 to 8 inches.

A portable version of the TSS 200 consists of the EcoStar Controller, Alpha 150 Cable Drum, SAT200 Tractor and with the TSS 200 conversion kit.



• Pressure Testing

Kampac II Leak Test System

Leak-Test System for single joint testing with air from 8" to 24" diameter. Integrated pan and tilt camera for accurate positioning. Pneumatically driven cable drum. Cable with integrated pressure hose.



Vario Kampac

Application range from 8" to 24" diameter. This system features an adjustable connecting rod between the two test bubbles, enabling longer sections of rehabilitated pipe to be leak-tested, adjustable range from approx. 8 ft to 23 ft. A pan and tilt camera between the two test bubbles assures accurate positioning and documentation of these test runs. Additionally, pipe connections between lateral and main line can be tested by carrying an extra lateral test bubble on the SAT-Star camera body which will be inserted from the main-line into the lateral. (Optional)

